



Compact Fluorescent
Energy Saver Reflector
Floods and Dimmable
Reflector Floods

*Ideal for indoor recessed
and track lighting and
outdoor fixtures*

ENERGY SAVER



Energy saver floods

Philips Compact Fluorescent Energy Saving Reflector and Dimmable Reflector Floods provide energy savings and reduce operating costs without sacrificing quality of light compared to incandescent equivalents.

Direct replacement for incandescent bulbs

- Provides warm and inviting soft white light
- Fits into incandescent fixtures
- Dimmable reflector—dims down to 10%

Long life

- Lasts 7 years*

Energy savings

- Saves up to \$49 over the life of the lamp when you replace an 85W PAR38 incandescent reflector with a 23W energy saver PAR38 reflector.**

* Based on an average daily usage of 3 hours per day, 7 days per week.

** Energy savings based on wattage saved x replacement lamp rated average life (8000 hours) ÷ 1000 x \$0.10 kWh rate.

PHILIPS
sense and simplicity

Compact Fluorescent Energy Saver Reflector Floods & Dimmable Reflector Floods

Ordering, Electrical and Technical Data

| Product Number | Description | Volts | Nom. Watts | Approx. Incand. Equiv. | Base | Color Temp. (Kelvin) | CRI | Approx. Initial Lumens ¹ | MOL (In.) | Diam. (In.) | Rated Avg. Life (Hrs.) ² | Min. Starting Temp. | Max. Ambient Temp. |
|----------------|-------------------------------------|-------|------------|------------------------|------|----------------------|-----|-------------------------------------|-----------|-------------|-------------------------------------|---------------------|--------------------|
| ◆ 15701-6 | Reflector Flood EL/A R20 | 120 | 14 | 50R20 | Med. | 2700 | 82 | 500 | 4 3/8 | 2.5 | 8000 | -4°F/-20°C | 122°F/50°C |
| ◆ 15703-2 | Reflector Flood EL/A R30 | 120 | 15 | 65BR30 | Med. | 2700 | 82 | 750 | 5 3/4 | 3.7 | 8000 | -4°F/-20°C | 122°F/50°C |
| ◆ 13707-5 | Reflector Flood EL/A R30 Dimmable | 120 | 16 | 65BR30 | Med. | 2700 | 82 | 630 | 5 13/32 | 3.7 | 8000 | -4°F/-20°C | 122°F/50°C |
| ◆ 15702-4 | Reflector Flood EL/A R40 | 120 | 23 | 85BR40 | Med. | 2700 | 82 | 1250 | 6 1/2 | 4.7 | 8000 | -4°F/-20°C | 122°F/50°C |
| ◆ 13708-3 | Reflector Flood EL/A R40 Dimmable | 120 | 20 | 85BR40 | Med. | 2700 | 82 | 900 | 6 3/32 | 4.7 | 8000 | -4°F/-20°C | 122°F/50°C |
| ◆ 15715-6 | Reflector Flood EL/A PAR38 | 120 | 23 | 85PAR38 | Med. | 2700 | 82 | 1250 | 6 1/2 | 4.7 | 8000 | -4°F/-20°C | 122°F/50°C |
| ◆ 14644-9 | Reflector Flood EL/A PAR38 Dimmable | 120 | 20 | 75PAR38 | Med. | 2700 | 82 | 850 | 6 3/32 | 4.7 | 8000 | -4°F/-20°C | 122°F/50°C |
| ◆ 15716-4 | Reflector Flood EL/A PAR38 Outdoor | 120 | 23 | 85PAR38 | Med. | 2700 | 82 | 1300 | 4 1/2 | 4.7 | 8000 | -4°F/-20°C | 122°F/50°C |

Shipping Data

| Product Number | SKU UPC (0-46677) | Outer Bar Code (5-00-46677) | Case Qty. | Case Weight (lbs.) | Case Cube (cu. ft.) | Pallet Qty. | SKUs Per Layer | Layers High | SKU Dimensions (W x D x H)(In.) | Case Dimensions (W x D x H)(In.) | Pallet Dimensions (W x D x H)(In.) |
|----------------|-------------------|-----------------------------|-----------|--------------------|---------------------|-------------|----------------|-------------|---------------------------------|----------------------------------|------------------------------------|
| 15701-6 | 15701-2 | 15701-7 | 6 | 6.0 | 0.178 | 1554 | 222 | 7 | 2.6 x 2.6 x 5.4 | 5.9 x 8.5 x 6.1 | 40.0 x 46.9 x 43.0 |
| 15703-2 | 15703-6 | 15703-1 | 6 | 1.95 | 0.487 | 450 | 90 | 5 | 4.2 x 4.2 x 5.9 | 9.0 x 13.3 x 7.1 | 39.8 x 45.0 x 35.3 |
| 13707-5 | 13707-6 | 13707-1 | 6 | 1.5 | 0.400 | 840 | 120 | 7 | 3.8 x 3.8 x 6.2 | 8.1 x 12.1 x 7.0 | 40.3 x 48.5 x 49.0 |
| 15702-4 | 15702-9 | 15702-4 | 6 | 2.60 | 0.889 | 216 | 54 | 4 | 5.4 x 5.4 x 7.0 | 11.4 x 16.8 x 8.1 | 39.5 x 44.9 x 32.2 |
| 13708-3 | 13708-3 | 13708-8 | 6 | 2.14 | 0.551 | 546 | 78 | 7 | 4.8 x 4.8 x 6.0 | 9.9 x 14.7 x 6.6 | 39.3 x 49.8 x 45.9 |
| 15715-6 | 15715-9 | 15715-4 | 6 | 3.20 | 0.889 | 216 | 54 | 4 | 5.4 x 5.4 x 7.0 | 11.4 x 16.8 x 8.1 | 39.5 x 44.9 x 32.2 |
| 14644-9 | 14644-3 | 14644-8 | 6 | 2.52 | 0.551 | 504 | 72 | 7 | 4.8 x 4.8 x 6.0 | 9.9 x 14.7 x 6.6 | 39.5 x 44.1 x 45.9 |
| 15716-4 | 15716-6 | 15716-1 | 6 | 3.20 | 0.560 | 432 | 72 | 6 | 4.5 x 4.5 x 5.9 | 9.9 x 14.6 x 6.7 | 39.8 x 43.7 x 40.1 |

- 1) Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.
 2) Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.
- ◆ Amalgam Technology provides stable light output from -4°F to 122°F.
 - ◆ ENERGY STAR® Bulb: As an ENERGY STAR® Partner, Philips has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.
 - ◆ Do not use with dimmers.
- Above specifications subject to change without notice.

WARNINGS & CAUTIONS: Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires a weather-protected fixture. Turn off power before changing bulb. This device complies with Part 18 of the FCC Rules.

Reliable operating temperature range -4F/-20C to 122F/50C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

| Bulb Type | Table/Floor Lamp | Outdoor Postlight | Wall Sconce | Surface Mount | Reading Lamp | Border Lights | Recessed Fixture | Open Hanging | Vanity Strip | Ceiling Fan |
|--------------------------|------------------|-------------------|-------------|---------------|--------------|---------------|------------------|--------------|--------------|-------------|
| Decorative Twister | ● | | ● | | | | | ● | | |
| Universal | ● | ● | ● | ● | ● | ● | ● | ● | | |
| 3-Way | ● | | | | | | | | | |
| Reflector Flood | | | | | | | ● | ● | | |
| Dimmable Reflector Flood | | | | | | | ● | ● | | |
| Candle | | ● | ● | | ● | | | | | ● |
| Vanity & Decor Globe | | | | | | | | ● | ● | ● |
| Soft White Plus | ● | ● | ● | | ● | ● | | ● | | ● |
| Outdoor | | ● | | | | ● | | | | |
| Bug-A-Way | | ● | | | | | | | | |
| Circline | ● | | | | | | | | | |
| Genie | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |



© 2008 Philips Lighting Company. All rights reserved.
 Printed in USA 1/08
 P-8516-C
www.philips.com

Philips Lighting Company
 200 Franklin Square Drive
 P.O. Box 6800
 Somerset, NJ 08875-6800
 1-800-555-0050
 A Division of Philips Electronics North America Corporation

Philips Lighting
 281 Hillmount Road
 Markham, Ontario
 Canada L6C 2S3
 1-800-555-0050
 A Division of Philips Electronics Ltd.